



## DUCAR 212 RULE PACKAGE

1. Engine must be factory rated Ducar 212cc and run in box stock configuration. All parts must be stock OEM factory production parts unless otherwise specified in these rules. No alteration, cutting, grinding or machining of any parts. No sandblasting, tumbling, or polishing of any kind. This is strictly prohibited. All parts are subject to be checked by a known stock part if in question. No reading between the lines. If it is not specifically mentioned in these rules, then it **MUST** remain stock.
2. Gas: 87 octane pump gas only (Track to supply test sample).
3. Block: Stock OEM Ducar 212 block with no machining allowed with the exception of cylinder clearance. Maximum bore size 2.758" 0 piston pop up allowed.
4. Cylinder Head: No machining permitted on gasket surface and absolutely no porting of any kind. Maximum intake valve head diameter 1.062" +/- .005" Maximum exhaust valve size .946" +/- .005" Minimum depth from gasket mating surface to combustion chamber between valves is .485" +/- .010" (for reference only). The seats must be stock and can have the 3 angles of 30/45/60 as from the factory. However, you may not attempt to excessively sink the valves in an effort to increase airflow. Stock OEM graphite style head gasket only. Minimum .042" thickness. No sealer.
5. Piston & Rings: Stock OEM dished piston with valve relief on exhaust side only. Maximum size 2.7565" measured at the bottom of the skirt. Stock OEM rings. No altering of the rings allowed, especially the oil ring.
6. Rod: Stock OEM cast connecting rod only. Rod may be honed for oil clearance only. No rounded or broken edges. No billet rods allowed.
7. Crankshaft: Stock unaltered OEM crankshaft. Governor gear may be removed. Max stroke 2.163 +/- .010".
8. Flywheel: Engine must run PVL aluminum die cast flywheel or Ducar aluminum die cast flywheel (DUCAR-FW) only. No cast iron OEM flywheels. Must utilize stock unaltered timing key. Stock OEM unaltered ignition coil.
9. Camshaft: Must run stock OEM camshaft. Base circle size .865" +.010 - .005" Maximum Intake lift .225 Maximum In duration at .050" = 210 Maximum In duration @ .200 = 75 Maximum Ex lift .232" Maximum Ex duration @ .050" = 212 Maximum Ex duration @ .200" = 84 All checks to be taken at the push rod.
10. Valve Train: Maximum valve spring wire diameter .079" Stock OEM springs must be used. (15lb @ .850" reference only) Valve seal allowed on intake side only. No shims

allowed. Stock OEM push rods must be used with a maximum length of 5.825" +.010"  
Stock unaltered lifters and spring retainers to be used. No lightweight components.

11. Carburetor: Stock OEM Ruixing carb only. Carb must be completely stock. No machining of any kind. Maximum venturi .615" and minimum venturi size .608" Carb bore maximum .750" Stock E-tube with a maximum of 20 holes. 1.092" minimum length and minimum outside diameter of .154" .066" maximum hole through the E-tube. Butterfly minimum .037" Minimum throttle shaft .115" Minimum screw length .305" Phenolic spacer must remain stock. Maximum pilot jet size .018" (.019" no-go) and must use both o-rings. Maximum main jet size .029" (.030" no-go)
12. Air Box: Stock OEM air box must be used and in stock unaltered form only. Air must enter through the air filter only. Any open unused holes must be plugged. Stock OEM air filter with foam sock must be used.
13. Muffler: Stock OEM muffler in unaltered form must be used. If any doubts about the integrity of the muffler should arise, simply cut the muffler in two, to determine legality by comparing to known stock muffler.
14. Governor: As of March 1st, 2024 competitors may utilize the DUCAR OEM rev limiting ignition coil (Part # 212-1260R) as an alternate to the stock OEM governor. You may remove the governor assembly completely and plug holes or leave the governor assembly in stock form. However, if you remove the governor, you MUST use the rev limiting coil. Effective 01/01/2025: Engine is NO LONGER required to be free revved in post-race tech. (If a competitor is suspected of exceeding a reasonable rpm (5500rpm) during the race, the tech official may look at the maximum rpm the competitor raced and ensure the rpm did not exceed 5500 rpm. If it does exceed 5500 rpm during the race, it would be considered a DQ.)
15. Gas Tank: Stock tank should be removed and an auxiliary tank mounted in the floor pan should be used. A top plate and fuel pump are allowed with the pump be pulsed off the valve cover only. (Track Option) Utilize stock OEM tank with the vent tube unplugged and up to 4 - 1/8" holes in the fuel cap for venting.
16. Low oil shutoff can be disconnected and/or completely removed. No taping or decals added to the recoil in an attempt to block off air.
17. Chain guard, throttle linkage, top plate and fuel pump are the only aftermarket parts allowed on the engine.
18. There is no longer a claimer rule. The engine in question must be protested by a competitor or subject to tech by the track if the promoter/tech deems necessary. The protest and acceptance fees are to be determined by the track.
19. If there is any doubt as to the legality of any part on a Ducar 212 engine, the competitor has the right to file a protest with the track/official. The part in question can then be shipped to DynoCams for review. Please include contact information for the promoter and we will contact the promoter with our findings on the legality of the part in question in a timely manner.