



00-6

CAM TECH SHEET

DESCRIPTION:

Exhaust lobe has softer opening ramp to help reduce lifter bore breakage. Extra duration has been added to exhaust closing to enhance top end. The intake lobe is the proven fast ramp 95-3. Billet lifters recommended. Good cam for unrestricted classes.

SPECS:

Cam Design: 00-6
Engine: Briggs 5HP Flathead
Class: Junior/Stock
Target RPM: 6200/6500
Valve Lash (In/Ex): .005in
Spring Pressure (In/Ex): 18 lbs / 17 lbs
Ignition Timing: 29-30 Deg BTDC

PROFILE:

Intake			Exhaust		
020	11.5	BTDC	020	48	BBDC
050	3	BTDC	050	37.5	BBDC
100	12	ATDC	100	20.5	BBDC
150	30.5	ATDC	150	1.5	BBDC
200	56	ATDC	200	22.5	ABDC
MAX LIFT	0.2325	INCH	MAX LIFT	0.2325	INCH
200	34.5	BBDC	200	66	BTDC
150	7.8	BBDC	150	41	BTDC
100	12	ABDC	100	22	BTDC
050	30	ABDC	050	5	BTDC
020	48	ABDC	020	11.5	ATDC
IN OPEN	16	BTDC	EX OPEN	56	BBDC
IN CLOSE	75	BTDC	EX CLOSE	21	ATDC
IN C/L	100.7	ATDC	EX C/L	111	BTDC
EZ START	51.5	ABDC	EZ DUR	33.5	DEG
EZ STOP	85	ABDC	EZ LIFT	0.015	INCH