



110-SS

CAM TECH SHEET

DESCRIPTION:

If you're running a class where there is no profile check, but can only have a running lift of .233, this may be the cam you are looking for. Excellent as a hot stock cam.

SPECS:

Cam Design:	110-SS
Engine:	Briggs 5HP Flathead
Class:	Hot Stock
Target RPM:	7000
Valve Lash (In/Ex):	.009 in
Spring Pressure (In/Ex):	20 lbs/ 20 lbs
Recommended Spring:	DCS1460
Ignition Timing:	30-32 Deg BTDC

PROFILE:

Intake			Exhaust		
020	35	BTDC	020	72	BBDC
050	24	BTDC	050	61	BBDC
100	8	BTDC	100	45	BBDC
150	10.5	ATDC	150	26.5	BBDC
200	33.5	ATDC	200	2	BBDC
MAX LIFT	0.239	INCH	MAX LIFT	0.239	INCH
200	2	BBDC	200	40	BTDC
150	22	ABDC	150	16	BTDC
100	40	ABDC	100	3	ATDC
050	56	ABDC	050	20	ATDC
020	67.5	ABDC	020	30	ATDC
IN OPEN	40	BTDC	EX OPEN	78	BBDC
IN CLOSE	74	ABDC	EX CLOSE	35	ATDC
IN C/L	106	ATDC	EX C/L	111	BTDC
DUR AT 050	260	DEG	DUR AT 050	260	DEG