



233-SS

CAM TECH SHEET

DESCRIPTION:

If you're looking for a cam with a maximum profile lift of .233 and no profile check, this is the cam. Aftermarket valve springs and billet lifters should be used.

SPECS:

Cam Design:	233-SS
Engine:	Briggs 5HP Flathead
Class:	Hot Stock
Target RPM:	7000
Valve Lash (In/Ex):	.010in
Spring Pressure (In/Ex):	20 lbs/ 20 lbs
Recommended Spring:	DCS1460
Ignition Timing:	30-32 Deg BTDC

PROFILE:

Intake			Exhaust		
020	36	BTDC	020	72.5	BBDC
050	25	BTDC	050	61.5	BBDC
100	9	ATDC	100	45	BBDC
150	10	ATDC	150	26	BBDC
200	34	ATDC	200	1	BBDC
MAX LIFT	0.233	INCH	MAX LIFT	0.233	INCH
200	5.5	BBDC	200	41.5	BTDC
150	20	ABDC	150	16	BTDC
100	39	ABDC	100	3	BTDC
050	54.5	ABDC	050	19	ATDC
020	66.5	ABDC	020	29.5	ATDC
IN OPEN	41	BTDC	EX OPEN	78	BBDC
IN CLOSE	73	ABDC	EX CLOSE	35.5	ATDC
IN C/L	105	ATDC	EX C/L	111	BTDC
DUR AT 050	260	DEG	DUR AT 050	260	DEG