

**375****CAM TECH SHEET****DESCRIPTION:**

If you are looking for a hard pulling modified cam with around .375 running lift with a retarded intake lobe, this is the cam for you.

SPECS:

Cam Design:	375
Engine:	Briggs 5HP Flathead
Class:	Jr. Drag/Limited/Open
Target RPM:	9000
Valve Lash (In/Ex):	.007 in / .008 in
Spring Pressure (In/Ex):	32-34 lbs/ 32-34 lbs
Recommended Spring:	DCSSH
Ignition Timing:	34-36 Deg BTDC

PROFILE:

Intake			Exhaust		
020	28	BTDC	020	72.5	BBDC
050	18.5	BTDC	050	61.5	BBDC
100	7.2	BTDC	100	48.1	BBDC
150	5	ATDC	150	35.5	BBDC
200	17	ATDC	200	22	BBDC
250	31.6	ATDC	250	7.3	BBDC
300	48.5	ATDC	300	9.9	ABDC
350	72.1	ATDC	350	33.4	ABDC
MAX LIFT	0.381	INCH	MAX LIFT	0.384	INCH
350	30.5	BBDC	350	68.3	BTDC
300	7.5	BBDC	300	45	BTDC
250	9	ABDC	250	28	BTDC
200	23	ABDC	200	13.4	BTDC
150	35.6	ABDC	150	0.4	BTDC
100	47.3	ABDC	100	11.8	ATDC
050	58.8	ABDC	050	24	ATDC
020	68.6	ABDC	020	35	ATDC
IN OPEN	38	BTDC	EX OPEN	80	BBDC
IN CLOSE	76	ABDC	EX CLOSE	44	ATDC
IN C/L	110.6	ATDC	EX C/L	107.5	BTDC
DUR @ 050	257.3	DEG	DUR @ 050	265	DEG