

**95-6****CAM TECH SHEET****DESCRIPTION:**

This fast ramp, short duration cam works well in a rookie motor. If you are looking for bottom and mid-range, this may be the cam for you. We recommend billet lifters be used and tappet bores beefed up.

SPECS:

Cam Design:	95-6
Engine:	Briggs 5HP Flathead
Class:	Purple/Blue
Target RPM:	5000/5600
Valve Lash (In/Ex):	.009in/.005in
Spring Pressure (In/Ex):	16 lbs / 15 lbs
Ignition Timing:	32-34 Deg BTDC

PROFILE:

Intake			Exhaust		
020	11	BTDC	020	43	BBDC
050	3	BTDC	050	35	BBDC
100	12.5	ATDC	100	19.5	BBDC
150	30	ATDC	150	1	BBDC
200	55.5	ATDC	200	23.5	ABDC
MAX LIFT	0.2325	INCH	MAX LIFT	0.2325	INCH
200	34.5	BBDC	200	66.5	BTDC
150	8	BBDC	150	41.5	BTDC
100	11.5	ABDC	100	22.5	BTDC
050	29.5	ABDC	050	5	BTDC
020	47	ABDC	020	7.5	ATDC
IN OPEN	14	BTDC	EX OPEN	47	BBDC
IN CLOSE	82	BTDC	EX CLOSE	14	ATDC
IN C/L	100	ATDC	EX C/L	111	BTDC
EZ START	50	ABDC	EZ DUR	35	DEG
EZ STOP	85	ABDC	EZ LIFT	0.015	INCH