

**98-3****CAM TECH SHEET****DESCRIPTION:**

The 98-3 is a good all-around cam for the stock and super stock classes. It also works well on road courses. This cam is easy on the valve train and the tappet bores.

SPECS:

Cam Design:	98-3
Engine:	Briggs 5HP Flathead
Class:	Junior/Stock/Super Stock
Target RPM:	6200/6500/7200
Valve Lash (In/Ex):	.005in
Spring Pressure (In/Ex):	16 lbs /15 lbs (Junior) 18 lbs/ 17lbs (Stock) 22 lbs/20 lbs (Super Stock)
Ignition Timing:	27-28 Deg BTDC

PROFILE:

Intake			Exhaust		
020	15	BTDC	020	52.5	BBDC
050	5	BTDC	050	37.5	BBDC
100	11.5	ATDC	100	20	BBDC
150	30	ATDC	150	1	BBDC
200	55.5	ATDC	200	24	ABDC
MAX LIFT	0.2325	INCH	MAX LIFT	0.2325	INCH
200	35	BBDC	200	66	BTDC
150	8.5	BBDC	150	41.5	BTDC
100	11.5	ABDC	100	22.5	BTDC
050	30	ABDC	050	5	BTDC
020	47	ABDC	020	11	ATDC
IN OPEN	21	BTDC	EX OPEN	60	BBDC
IN CLOSE	76	BTDC	EX CLOSE	20	ATDC
IN C/L	101	ATDC	EX C/L	111	BTDC
EZ START	51	ABDC	EZ DUR	34	DEG
EZ STOP	85	ABDC	EZ LIFT	0.015	INCH